ERGO-LIFTER/ELECTRIC SKID LIFTER

COMFORT NEVER WORKED SO HARD



- » Both models come with a quick-lift feature to reduce pump strokes.
- » The electric model has a push button operated lift.
- » The electric model can easily maneuver in a lowered position and lock itself in place to remain stationary.
- » It also comes with a deep cycle battery and built in charger.





ERGO-I

ANUAL SKID LIFTER/ELECTRIC SKID LIFTEI

FOR ORDERS OR INQUIRIES CALL 1.800.558.6012 OR EMAIL HPTORDERS@LIFTRITE.COM

ERGONOMICS

Lift pallets, skids or containers 31.5 inches off the ground at the push of a button.

MAINTAINABILITY

Equipped with a stroke bypass and overload valve, you can feel confident you aren't lifting a load too heavy.

PRODUCTIVITY

The electric lift is powered by a 12V DC hydraulic power pack (electric model).

STANDARD SPECIFICATIONS:

- » Capacity: 3,000 lbs
- » Low Height: 3.25 inches
- » Raised Height: 31.50 inches
- » Wheel Diameter: 8.00 inches
- » Wheel Type: Polyurethane
- » Roller Diameter: 3.00 inches
- » Roller Type: Nylon

MANUAL OPTIONS:

EM11LY00-000

- » Frame Width: 27.00 inches
- » Fork Length: 48 inches
- » Fork Width: 7.0 inches
- » Weight: 340 lbs

EM21LY00-000

- » Frame Width: 20.50 inches
- » Fork Length: 48 inches
- » Fork Width: 7.0 inches
- » Weight: 330 lbs

ELECTRIC OPTIONS:

EE11LY00-000

- » Frame Width: 27.00 inches
- » Fork Length: 48 inches
- » Fork Width: 7.0 inches
- » Weight: 440 lbs

EE21LY00-000

- » Frame Width: 20.50 inches
- » Fork Length: 48 inches
- » Fork Width: 7.0 inches
- » Weight: 430 lbs



Polyurethane wheels and rollers



Tear-drop handle



Manually operated pump with quick lift

Durable powder coat paint finish

Due to continuous product improvement, specifications are subject to change without notice or obligation. Some systems and features shown are optional at extra cost. Lift-Rite is a U.S. trademark of Lift-Rite.



W A R E H O U S E www.totalwarehouse.com 833-868-2500

