

### 346 Basic dimensions







Width (all models):

- -42" Cushion tires
- -46" SE tires

## Available models (36-volt & 48-volt)



### Three-wheel configuration

Model	Capacity	Height	Length	
E18	3,500 lb	80"	79"	
E20	4,000 lb	80"	79"	









Lift-out	36-volt  850 AH  18-85-21  18-100-21	48-volt  595 AH  24-85-15  24-100-15	
Slide-out Slide pad adds 0.25"	36-volt  850 AH  18-85-21  18-100-21	48-volt  595 AH  24-85-15  24-100-15	
Roll-out Rollers add 2.25"	36-volt  850  AH  18-85-21	48-volt 595 AH 24-85-15	

\*AH capacity using standard, 6-hour rate

## **Operator compartment**



#### **Features**

- Small diameter steering wheel
- Large diameter cup holder
- Tool storage compartments
- Ergonomics for wide range of drivers
- Informational display unit





### **Operator compartment**

Linde Material Handling

- Driver comfort leads to highproductivity
- Full-suspension seat (standard)
- Adjustable armrest with fingertip controls
- Small diameter steering wheel
- Low step height for easy entry/exit





**Competition**Non-suspension
Semi-suspension



## **Ergonomic features**

Linde

Linde Material Handling

- Adjustable steering column
- Tilt-up armrest with fingertip controls
- Easy entry/exit on both sides
  - Left-side PRIMARY
  - Right-side SECONDARY
- Adjustable, full-suspension seat



