



IRONCLAD®

UNIQUE SQUARE TUBE TECHNOLOGY



The unique square tube technology at work in IRONCLAD® batteries has up to 84% more positive-plate surface area vs. round tubular and flat-plate batteries. More surface area means more power, so IRONCLAD batteries sustain higher voltages than similarly sized conventional batteries. Industry-leading amp-hour capacities can help trucks lift and drive faster, and last longer into the shift.

Developed for demanding applications and loads, IRONCLAD Loadhog® batteries were the first to pack 100 amp-hours into a standard 85-AH compartment. That's up to 18% more capacity than similarly sized conventional batteries – more than enough to keep running strong through the toughest shifts.



Technical Data Sheet



With 55, 75, 100 and 140 amp-hour plates, Loadhog® batteries are designed to handle more demanding shifts and loads.



HEAVY-DUTY POWER

Engineered for heavy-duty applications and shifts



AMP HOURS

Up to 18% higher amp-hour capacity than conventional batteries



RUN TIMES

Extended run times allow trucks to last longer into the shift



LIMITED WARRANTY

Up to 5-year +1 warranty depending on charging applications

E55L - Square Tubular (55 AH per Positive Plate)

No. of Plates	Cell Catalog #	Capacity @ 6 hr. Rate @ 77°F or 5 hr. Rate @ 30°C to 1.70 Vpc		Base Dimensions of Cells*				Weight of Electrolyte		Approx. Weight Per Cell**	
				Length		Width		lbs	kg	lbs	kg
				in	mm	in	mm				
5	93478-CW	0.21	110	2.00	51	6.19	157	5.4	2.4	23	10.4
7	93479-CW	0.32	165	2.75	70	6.19	157	5.8	2.6	31	14.1
9	93480-CW	0.42	220	3.50	89	6.19	157	6.2	2.8	36	16.3
11	93481-CW	0.53	275	4.25	108	6.19	157	6.7	3.0	44	20.0
13	93482-CW	0.64	330	5.00	127	6.19	157	8.5	3.9	52	23.6
15	93483-CW	0.74	385	5.75	146	6.25	159	10.0	4.5	58	26.3
17	93484-CW	0.85	440	6.50	165	6.25	159	11.0	5.0	70	31.8
19	93485-CW	0.96	495	7.25	184	6.25	159	12.0	5.4	78	35.4
21	93486-CW	1.06	550	8.00	203	6.25	159	13.5	6.1	85	38.6
23	93487-CW	1.17	605	8.75	222	6.25	159	15.0	6.8	94	42.6
25	93488-CW	1.27	660	9.50	241	6.25	159	16.0	7.3	102	46.3
27	93489-CW	1.38	715	10.25	260	6.25	159	17.5	7.9	111	50.4
29	93490-CW	1.49	770	11.00	279	6.25	159	19.0	8.6	119	54.0
31	93491-CW	1.59	825	11.75	298	6.25	159	20.5	9.3	127	57.6
33	93492-CW	1.70	880	12.50	318	6.25	159	22.0	10.0	133	60.3

Standard coverless battery height is 14.87" over lifting ear

* Tray, tray partitions and required clearance make complete batteries up to 1.00" longer and wider than cells alone

** Including steel tray

E75L - Square Tubular (75 AH per Positive Plate)

No. of Plates	Cell Catalog #	Capacity @ 6 hr. Rate @ 77°F or 5 hr. Rate @ 30°C to 1.70 Vpc		Base Dimensions of Cells*				Weight of Electrolyte		Approx. Weight Per Cell**	
				Length		Width		lbs	kg	lbs	kg
				in	mm	in	mm				
5	83623-CW	0.29	150	2.00	51	6.19	157	4.0	1.8	25	11.3
7	90000-CW	0.43	225	2.75	70	6.19	157	5.8	2.6	37	16.8
9	90001-CW	0.58	300	3.50	89	6.19	157	7.6	3.4	47	21.3
11	90002-CW	0.72	375	4.25	108	6.19	157	9.4	4.3	58	26.3
13	90003-CW	0.87	450	5.00	127	6.19	157	11.2	5.1	68	30.8
15	90004-CW	1.01	525	5.75	146	6.25	159	12.9	5.9	79	35.8
17	90005-CW	1.16	600	6.50	165	6.25	159	14.4	6.5	90	40.8
19	90006-CW	1.30	675	7.25	184	6.25	159	16.4	7.4	100	45.4
21	90007-CW	1.45	750	8.00	203	6.25	159	18.2	8.3	111	50.3
23	90008-CW	1.59	825	8.75	222	6.25	159	20.0	9.1	121	54.9
25	90009-CW	1.74	900	9.50	241	6.25	159	21.8	9.9	132	59.9
27	90010-CW	1.88	975	10.25	260	6.25	159	23.5	10.7	143	64.9
29	90011-CW	2.03	1050	11.00	279	6.25	159	25.3	11.5	155	70.3
31	90012-CW	2.17	1125	11.75	298	6.25	159	27.1	12.3	163	73.9
33	90013-CW	2.32	1200	12.50	318	6.25	159	28.9	13.1	171	77.6

Standard coverless battery height is 18.94" over lifting ear

E100 - Square Tubular (100 AH per Positive Plate)

No. of Plates	Cell Catalog #	Capacity @ 6 hr. Rate @ 77°F or 5 hr. Rate @ 30°C to 1.70 Vpc		Base Dimensions of Cells*				Weight of Electrolyte		Approx. Weight Per Cell**	
				Length		Width		lbs	kg	lbs	kg
				in	mm	in	mm				
5	95621-CW	0.39	200	2.00	51	6.19	157	6.3	2.9	34	15.4
7	95622-CW	0.58	300	2.75	70	6.19	157	8.4	3.8	47	21.3
9	95623-CW	0.77	400	3.50	89	6.19	157	10.5	4.8	60	27.2
11	95624-CW	0.97	500	4.25	108	6.19	157	12.5	5.7	73	33.1
13	95625-CW	1.16	600	5.00	127	6.19	157	14.6	6.6	86	39.0
15	95626-CW	1.35	700	5.75	146	6.25	159	17.8	8.1	99	44.9
17	95627-CW	1.54	800	6.50	165	6.25	159	19.9	9.0	113	51.3
19	95628-CW	1.74	900	7.25	184	6.25	159	21.9	9.9	126	57.2
21	95629-CW	1.93	1000	8.00	203	6.25	159	24.1	10.9	140	63.5
23	95630-CW	2.12	1100	8.75	222	6.25	159	27.2	12.3	152	68.9
25	95631-CW	2.32	1200	9.50	241	6.25	159	29.3	13.3	166	75.3
27	95632-CW	2.51	1300	10.25	260	6.25	159	31.4	14.2	180	81.6
29	95633-CW	2.70	1400	11.00	279	6.25	159	34.5	15.6	195	88.5
31	95634-CW	2.90	1500	11.75	298	6.25	159	36.6	16.6	206	93.4
33	95635-CW	3.09	1600	12.50	318	6.25	159	38.7	17.6	216	98.0

Standard coverless battery height is 22.81" over lifting ear

* Tray, tray partitions and required clearance make complete batteries up to 1.00" longer and wider than cells alone

** Including steel tray

E140 - Square Tubular (140 AH per Positive Plate)

No. of Plates	Cell Catalog #	Capacity @ 6 hr. Rate @ 77°F or 5 hr. Rate @ 30°C to 1.70 Vpc		Base Dimensions of Cells*				Weight of Electrolyte		Approx. Weight Per Cell**	
				Length		Width		lbs	kg	lbs	kg
				kWh	AH	in	mm	in	mm		
5	390200-CW	0.54	280	2.00	51	6.19	157	8.0	4.1	53	24.0
7	390201-CW	0.81	420	2.75	70	6.19	157	13.0	6.0	68	30.8
9	390202-CW	1.08	560	3.50	89	6.19	157	16.0	7.3	87	39.5
11	390203-CW	1.35	700	4.25	108	6.19	157	19.0	8.6	105	47.6
13	390204-CW	1.62	840	5.00	127	6.19	157	22.0	10.0	120	54.4
15	390205-CW	1.89	980	5.75	146	6.25	159	26.0	11.3	136	61.7
17	390206-CW	2.16	1120	6.50	165	6.25	159	29.0	13.2	154	69.9
19	390207-CW	2.43	1260	7.25	184	6.25	159	33.0	15.0	172	78.0
21	390208-CW	2.70	1400	8.00	203	6.25	159	37.0	16.8	191	86.6
23	390209-CW	2.97	1540	8.75	222	6.25	159	41.0	18.6	207	93.9
25	390210-CW	3.24	1680	9.50	241	6.25	159	45.0	20.4	223	101.2
27	390211-CW	3.51	1820	10.25	260	6.25	159	48.0	22.2	239	108.4
29	390212-CW	3.78	1960	11.00	279	6.25	159	53.0	24.0	255	115.7

Standard coverless battery height is 30.56" over lifting ear
 * Tray, tray partitions and required clearance make complete batteries up to 1.00" longer and wider than cells alone
 ** Including steel tray



TOTAL
WAREHOUSE

www.enersys.com

© 2020 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates except UL, which is not the property of EnerSys. Subject to revisions without prior notice. E.&O.E.
 AM-ICLH-TD AA September 2020

