



FLOODED
LEAD ACID

IRONCLAD®

UNIQUE SQUARE TUBE TECHNOLOGY



The unique square tube technology at work in IRONCLAD® batteries has up to 84% more positive-plate surface area vs. round tubular and flat-plate batteries. More surface area means more power, so IRONCLAD batteries sustain higher voltages than similarly sized conventional batteries. Their industry-leading amp-hour capacities can help trucks lift and drive faster, and last longer into the shift.

IRONCLAD Superhog® batteries are supercharged performers built to handle the fastest runs, quickest lifts and heaviest loads. Superhog 220 to 2170 amp-hour batteries will last long enough to cut or eliminate premature battery change-outs.



Technical Data Sheet



With 110 and 155 amp-hour plates, Superhog® batteries will handle the most demanding applications with the fastest lift and travel speeds.



SUPER DUTY POWER

Engineered for the heaviest applications and shifts



AMP HOURS

Industry-leading amp hour capacity rating



RUN TIMES

Extended run times allow trucks to last longer into the shift



LIMITED WARRANTY

Up to 5-year +1 warranty depending on charging applications

E110 - Square Tubular (110 AH per Positive Plate)

No. of Plates	Cell Catalog #	Capacity @ 6 hr. Rate @ 77°F or 5 hr. Rate @ 30°C to 1.70 Vpc		Base Dimensions of Cells*				Weight of Electrolyte		Approx. Weight Per Cell**	
				Length		Width		lbs	kg	lbs	kg
				in	mm	in	mm				
5	95636-CW	0.42	220	2.00	51	6.19	157	6.4	2.9	35	15.9
7	95637-CW	0.64	330	2.75	70	6.19	157	8.6	3.9	48	21.8
9	95638-CW	0.85	440	3.50	89	6.19	157	10.7	4.9	61	27.7
11	95639-CW	1.06	550	4.25	108	6.19	157	12.8	5.8	74	33.6
13	95640-CW	1.27	660	5.00	127	6.19	157	14.9	6.8	88	39.9
15	95641-CW	1.49	770	5.75	146	6.25	159	18.2	8.3	101	45.8
17	95642-CW	1.70	880	6.50	165	6.25	159	20.3	9.2	115	52.2
19	95643-CW	1.91	990	7.25	184	6.25	159	22.3	10.1	129	58.5
21	95644-CW	2.12	1100	8.00	203	6.25	159	24.6	11.2	143	64.9
23	95645-CW	2.34	1210	8.75	222	6.25	159	27.7	12.6	155	70.3
25	95646-CW	2.55	1320	9.50	241	6.25	159	29.9	13.6	169	76.7
27	95647-CW	2.76	1430	10.25	260	6.25	159	32.0	14.5	184	83.5
29	95648-CW	2.97	1540	11.00	279	6.25	159	35.2	16.0	199	90.3
31	95649-CW	3.18	1650	11.75	298	6.25	159	37.3	16.9	210	95.3
33	95650-CW	3.40	1760	12.50	318	6.25	159	39.5	17.9	220	99.8

Standard coverless battery height is 22.81" over lifting ear

* Tray, tray partitions and required clearance make complete batteries up to 1.00" longer and wider than cells alone

** Including steel tray

E155 - Square Tubular (155 AH per Positive Plates)

No. of Plates	Cell Catalog #	Capacity @ 6 hr. Rate @ 77°F or 5 hr. Rate @ 30°C to 1.70 Vpc		Base Dimensions of Cells*				Weight of Electrolyte		Approx. Weight Per Cell**	
				Length		Width		lbs	kg	lbs	kg
				in	mm	in	mm				
5	390220-CW	0.60	310	2.00	51	6.19	157	8.2	3.7	54	24.5
7	390221-CW	0.90	465	2.75	70	6.19	157	13.3	6.0	69	31.3
9	390222-CW	1.20	620	3.50	89	6.19	157	16.3	7.3	88	39.9
11	390223-CW	1.50	775	4.25	108	6.19	157	19.4	8.7	107	48.5
13	390224-CW	1.79	930	5.00	127	6.19	157	22.4	10.1	121	54.9
15	390225-CW	2.09	1085	5.75	146	6.25	159	26.5	11.9	137	62.1
17	390226-CW	2.39	1240	6.50	165	6.25	159	29.6	13.3	156	70.8
19	390227-CW	2.69	1395	7.25	184	6.25	159	33.7	15.2	174	78.9
21	390228-CW	2.99	1550	8.00	203	6.25	159	37.7	17.0	193	87.5
23	390229-CW	3.29	1705	8.75	222	6.25	159	41.8	18.8	209	94.8
25	390230-CW	3.59	1860	9.50	241	6.25	159	45.9	20.7	225	120.1
27	390231-CW	3.89	2015	10.25	260	6.25	159	49.0	22.1	241	109.3
29	390232-CW	4.19	2170	11.00	279	6.25	159	54.1	24.4	257	116.6

Standard coverless battery height is 30.56" over lifting ear.

* Tray, tray partitions and required clearance make complete batteries up to 1.00" longer and wider than cells alone.

** Including steel tray



www.enersys.com

© 2020 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates except UL, which is not the property of EnerSys. Subject to revisions without prior notice. E.&O.E.
AM-ICSH-TD AA September 2020

